

Airgas.

RDA AHVP30-6M NA Manufacturers Series Positioner 3,000 lb capacity

Red-D-Arc's RDA AHVP30-6M NA positioners provide 360° rotation of a work piece along with 135° forward tilt to better position weldments for better down-hand or automatic welding. All-fabricated steel frames and bases support rotation and tilt spur-gears driven by worm-gear reducers to provide enhanced safety and durability. A remote hand pendant is used to control table-rotation direction and speed, and a stop-switch is included. The positioner-mounted control box has controls for table tilt as well as an e-stop control. Rotation motors are inverter-controlled variable-frequency AC-type, providing a full range of variable-speed control with excellent speed regulation. Red-D-Arc welding positioners are engineered to provide maximum safety and dependability and control boxes on M-series positioners have IP65-rated enclosures with full CE certification. The RDA AHVP30-6M NA's table can be set to one of three different table heights.



Specifications

Model RDA AHVP30-6M NA

Capacity 3307 lb (1.5 tonne) at 6 in (152 mm) C of G and 6 in (152 mm) eccentricity

Rotation Speed 0.07 - 1.4 RPM

Rotation Motor 0.75 kW inverter-controlled variable-frequency AC-type

Rotation Torque 19,525 in-lbs (2206 Nm)

Tilt 135° forward tilt in 30 seconds

Tilt Motor 0.75 kW with brake
Tilt Torque 39,050 in-lbs (4413 Nm)

Table Height (Horizontal) 33.7 in (855 mm), 39.6 in (1005 mm), 45.5 (1155 mm)

Table Diameter 36.2 in (920 mm) round with three 0.7 in (19 mm) slots

Hand Pendant Control Forward/stop/reverse/variable-speed table rotation control with 20 ft control cable

Control Panel Functions Tilt up/tilt down functions, e-stop and power on/off switch

Primary Input Power 110 V, 1 phase, 60 Hz

Input Current at Rated Load 4.6 A Ground Capacity 300 A

Weight 1984 lb (900 kg)

Control Box Ingress Protection Rating IP65

Options Remote foot controls, various capacity gripper chucks

CE 15 month


Red-D-Arc Welderentals, an Airgas company, rents and sells welding and weld-positioning equipment - around the world.

reddarc.com 1-866-733-3272







RDA AHVP30-6M NA Manufacturers Series Positioner




3000 lb capacity








Rotating



Load lb (tonne)	Eccentricity in (mm)
3300 (1.5)	6 (152)
2750 (1.25)	7 (178)
2200 (1)	9 (229)
1600 (0.72)	12 (305)
1100 (0.5)	17.5 (445)
550 (0.25)	35.5 (902)



Load lb (tonne)	C of G in (mm)
	, ,
3300 (1.5)	6 (152)
2750 (1.25)	8 (203)
2200 (1)	12 (305)
1600 (0.72)	18.5 (470)
1100 (0.5)	29.5 (750)
550 (0.25)	65 (1651)

reddarc.com

1-866-733-3272